

VIVIDLINE



Description

VividLine Wall Washer is a dynamic linear lighting solution designed to bring façades to life with vibrant color effects. Boasting a long lifespan of 50,000 hours @L70 and backed by a 5 year warranty, VividLine ensures reliable, high-quality illumination for years to come. This offers versatile lighting options, with RGB and CCT choices of 2700K, 3000K, and 4000K, allowing you to create stunning visual effects that enhance the architectural features of any building. Its wide 120° beam angle delivers a uniform wash of light, perfect for highlighting large surfaces with a smooth, consistent glow. Constructed from durable stainless steel and high-pressure die-cast materials, VividLine is built to withstand the elements. With an IP65 rating, this wall washer is ideal for outdoor use, performing reliably in various climates and conditions.

Product Benefits

Versatility and Lighting Effects
Exceptional Performance and Energy Efficiency
Innovative Design
Highly Versatile and Customized
Durability and Reliability

Application Areas

Dynamic Facade Lighting for Commercial / Residential Buildings
Accent Lighting for Architectural Lines / Surfaces Requiring Color Effects
Decorative Lighting for Public Spaces / Cultural Centers
Entertainment Venues

Product Data



General Information

Driver Included:	Yes
Lifespan:	50,000 hours @ L70
Warranty:	Up to 5 Year

Luminaire Performance

Power Consumption:	4W, 8W, 12W, 15W
Luminous Flux:	360 lm, 720 lm, 1,080 lm, 1,350 lm
Chipset Efficacy:	130 lm/W
Luminous Efficacy:	90 lm/W
Correlated Color Temperature:	2700K, 3000K, 4000K, RGB
Color Rendering Index (CRI):	>80
SDCM:	<3
Beam Angle:	120°

Operating and Electrical

Input Voltage:	DC24V
Power Factor (Fraction):	>0.9

Temperature

Operating Temperature:	-25°C – 50°C
Ambient Humidity:	10% – 90%


Controls and Dimming

Controls:	On/Off, DMX512
Dimming:	DALI, 0-10V

Mechanical and Housing	
Housing Material:	Stainless Steel Faceplate, High Pressure
	Die-casting Body, Surface with
	Electrostatic Plastic Coating
Installation:	Surface Mount

Compliance and Certifications	
Ingress Protection Code:	IP65
Impact Protection Code:	IK08
Certifications:	CE, CCC

Dimensions			
Power Consumption:	4W	8W	12W / 15W
LxWxH (mm):	330x16x34	500x16x34	1000x16x34



Head Office:
192-Y Block, Commercial Area, Phase III, DHA Lahore, Pakistan.

Sales Office:
120-Y Block, Commercial Area, Phase III, DHA Lahore, Pakistan.

