

Cable - Medium Voltage XLPE

Cable Description: 1 X 630 MM2 CIRCULAR COMPACT AL XLPE COPPER TAPE COPPER WIRE

SCREEN PVC AWA PVC BLACK : 8.7/15 KV IEC60502 PT 2 : SHEATHING

Design and Construction Data

Reference Manufacturing Standards	IEC 60228 IEC 60502 PT 2	
Max. Permissible Continuous Conductor Temp	°C	90
Max. Conductor Short Circuit Temp for 5 Seconds	°C	250
Rated Voltage ' Uo / U '	kV	8.7/15
Number of Conductors x Cross-Section	mm ²	1 x 630
Conductor Material & Shape	Aluminum & Stranded Class 2 Circular Compact Round Shape	
Insulation Material	XLPE	
Conductor Screen Thickness	mm	0.70
Insulation Nominal Thickness	mm	4.50
Insulation Screen Thickness	mm	0.70
Shield Material Type/Size	mm	Copper Tape / Wires
Bedding Material	PVC-ST2	
Bedding Nominal Thickness	mm	1.50
Armour Material Type	Aluminium Wire (AWA)	
Nominal Armour Wire Size	mm	2.50 -5%
Outer Sheath Material	PVC-ST2	
Sheath Material Thickness	mm	2.80
Colour of Outer Sheath	Black	
Approximate Cable Overall Diameter	mm	59.08
Approximate Cable Weight	Kg/km	4657
Cable Length	Meter	500 ± 5%

Electrical Data


Max Conductor DC resistance @ 20 °C	ohm/km	0.0469
Max Shield DC resistance @ 20 °C	ohm/km	0.524
High Voltage Test at 30.5kV for 5 min	No Breakdown Shall Occur	
Partial Discharge test (max)	pC	10
Max Phase Conductor Short Circuit Current @ 1 Second	kA	59.22
Current Carrying Capacity		
Laid in Free air @ 30 °C Ambient Temperature	Amp	844
Laid in Duct @ 20 °C	Amp	519
Laid in Ground @ 20 °C	Amp	543
Depth of laying in ground	m	0.80
Soil Thermal Resistivity	K.m/W	1.50
Minimum Bending Radius	mm	15 D
The Cable shall meet all Test requirements	IEC 60228 IEC 60502 PT 2 IEC 60332-1	

Cable Marking

1X630 MM SQ AL/XLPE/PVC/AWA/PVC 15 kV IEC 60228, 60502-2 FAST CABLES LTD Y.O.M - METER MARKED

Cable - Medium Voltage XLPE
Cable Description: 1 X 630 MM2 CIRCULAR COMPACT AL XLPE COPPER TAPE COPPER WIRE
SCREEN PVC AWA PVC BLACK : 8.7/15 KV IEC60502 PT 2 : SHEATHING

Cable Drawing



1 X 630 MM2 CIRCULAR COMPACT AL XLPE COPPER TAPE COPPER WIRE SCRE		Approx. Diameter
Stranded Aluminum Conductor with Round shape	mm	28.70~32.50
Xlpe Insulated	mm	40.90
Bedding	mm	48.08
Aluminium wire Armour (AWA)	mm	53.08
Outer Sheathing	mm	59.08